

EPS[®] 2121

DATA SHEET

ACRYLIC EMULSION

Description

EPS 2121 is an all acrylic general purpose pressure sensitive adhesive emulsion for removable applications. EPS 2121 exhibits low peel, moderate tack, and high shear values. Typical values below are for the neat polymer.

- ✓ 180 Peel (PSTC-101) 1.4 lbs/inch
- ✓ Loop Tack (PSTC-16) 2.3 lbs/square inch
- ✓ Static Shear (PSTC-107)* >10,000 minutes (1"x1"x1kg)

Specifications

Weight Solids: 50.00 ± 0.70%

Weight/Gallon: 8.50 ± 0.10

pH: 7.0 - 8.0

Tentative Properties

Volume Solids: 49.0 ± 0.70%

Tg: - 32°C (measured)

Acid Value (on solids): 19

Viscosity (#2 @ 20 rpm): 500 - 700 cps

Suggested Formulations

None

Questions? Call EPS Technical Service @ 1-800-601-8111

05-08-2014

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.