

EPS[®] 6684

LONG OIL ALKYD

DATA SHEET

Description

EPS 6684 is a long oil alkyd. EPS 6684 is designed to provide excellent flow, leveling and durability. This balance of properties makes EPS 6684 an excellent choice for architectural enamels and industrial maintenance paints.

- ✓ Excellent flow and leveling
- ✓ Excellent pigment wetting
- ✓ Fast dry
- ✓ Excellent adhesion

Specifications

Weight Solids: 60.0 ± 0.7%
Weight/Gallon: 7.70 ± 0.10
Viscosity: Y – Z₁
Acid Value:* 10 max
Color: 7 max

Suggested Drier Package

(% Metal on Resin Solids)

Cobalt	0.07
Calcium	0.05
Zirconium	0.40

Typical Properties

Volume Solids: 52.3 ± 0.7%
Oil Type: Soya
Modifier: None
Solvent Composition: LAMS/Xylene (38.1/1.9)
OH Value: 58 (theoretical)

Suggested Formulation

None

*Acid value on solids

05-09-2014

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option