

# EPS<sup>®</sup> 717

## DATA SHEET

### Description

EPS<sup>®</sup> 717 is a high solids all-acrylic polymer offering fast dry times and early water resistance. EPS<sup>®</sup> 717 is ideal for use exterior coatings, fascades, road line and tennis court marking.

### Properties

EPS<sup>®</sup> 717 dries very fast, is low in odor, has excellent early water and abrasion resistance combined with good exterior durability.

### Physical data

Solids by weight [%]:	55.0 ± 1
Viscosity, 23 °C [mPa·s]: (Brookfield, Spindle 2)	< 500
pH value [-]:	8.0 – 9.0

### Typical values

MFFT [°C]:	+ 17
Density @ 20 °C [kg/m <sup>3</sup> ]:	1071

### Storage

EPS<sup>®</sup> 717 should be stored in a closed container at a dry place at storage temperatures between 5 °C and 30 °C.

### Stability

Under the above mentioned storage condition the stability will be 6 months ex works.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Date of issue: March 2016