

# EPS<sup>®</sup> 730

# DATA SHEET

## Description

EPS<sup>®</sup> 730 is a very fine particle size, surfactant stabilized, acrylic copolymer in water.

## Properties

EPS<sup>®</sup> 730 offers excellent adhesion properties over powdery surfaces. It is recommended as a stabilizing solution when renovating old plasters and cement substrates.

## Physical data

Solids by weight [%]:	30.0 ± 1
Viscosity, 23 °C [mPa·s]: (Brookfield, Spindle 2)	< 500
pH value [-]:	8.0 – 9.0

## Typical values

MFFT [°C]:	0
Density @ 20 °C [kg/m <sup>3</sup> ]:	1055

## Storage

EPS<sup>®</sup> 730 should be stored in a closed container at a dry place at storage temperatures between 5 °C and 30 °C.

## Stability

Under the above mentioned storage condition the stability will be 12 months ex works.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Date of issue: August 2019